



- The most installation-friendly IP23 luminaire on the market
- Available with different options for control
- Made in Värnamo, Sweden



Tage G2 is the next generation of Swedish-made industrial luminaires in the Tage family! Tage G2 took its start in the popular Tage luminaire, with the goal of creating the market's most flexible and easy-to-install IP23 luminaire! With a low-build frame in zinc-coated sheet steel and end caps in recycled ABS + PET, the luminaire is as robust as Tage but at the same time very easy and tool-free access to the end caps during installation. The end caps also have a unique solution where cables never need to be passed through a cable gland and thanks to the end cap, IP23 is achieved and time saves time during installation. It also has a bracket for strain relief or installation aid of the cable. Tage G2 is available in two lengths (1300 / 1600mm) and with three different beam angles, 30°, 60° and 90°. The luminaire is available as ON/OFF, DALI or BTDA, 4000K and with LED in one or two rows (2R). The On/Off model has double luminous fluxes that are set with a dipswitch in one end. Tage G2 can be customized with e. g. painting in any RAL color or CRI90. BTDA stands for Bluetooth DALI and the luminaires communicate wirelessly with each other through a mesh network that relays information via the other luminaires. This provides stable signal strength and is also suitable for difficult environments for radio signals. Configuration of the luminaires is done using Bluetooth and the Exaktor Koolmesh app for iOS. The Tage G2 is available as a variant with a quick-connect terminal block or with a quick-connector. The On/Off and BTDA models have a 5-pin quick-connect terminal block in each end with 5G2.5mm² internal cabling. For DALI it is 5G2.5mm² + 2x1.5mm² for DALI BUS. With the quick-connector, Tage G2 is delivered with a male/female connector behind the cover in each end and then a cord rack with ready-made connectors is clicked in. Tage G2 therefore achieves IP23 even with quick connectors! Tage G2 is manufactured in Värnamo.

Do you need support?

offert@exaktor.se

0370-69 07 20

exaktor.com/en

Variations

| E-number | Product name | Max. system power (W) | Lumen (lm) | Colour temperature (K) | Mått (LxWxH/D, mm) | Colour | IP-class |
|----------|-------------------------------|-----------------------|---------------|------------------------|--------------------|-----------------|----------|
| 7219703 | TAGE G2 L13 60° 840 | 59 | 7000 - 9100 | 4000 | 1456x95x42 | Stainless steel | IP23 |
| 7219706 | TAGE G2 L13 90° 840 | 59 | 7100 - 9270 | 4000 | 1456x95x42 | Stainless steel | IP23 |
| 7219707 | TAGE G2 L13 60° 840 DALI | 59 | 7000 - 9100 | 4000 | 1456x95x42 | Stainless steel | IP23 |
| 7219708 | TAGE G2 L13 90° 840 DALI | 59 | 7100 - 9270 | 4000 | 1456x95x42 | Stainless steel | IP23 |
| 7219714 | TAGE G2 2R L13 60° 840 | 84 | 10000 - 13300 | 4000 | 1456x95x52 | Stainless steel | IP23 |
| 7219715 | TAGE G2 2R L13 90° 840 | 84 | 10170 - 13500 | 4000 | 1456x95x52 | Stainless steel | IP23 |
| 7219716 | TAGE G2 2R L13 60° 840 DALI | 84 | 10000 - 13300 | 4000 | 1456x95x52 | Stainless steel | IP23 |
| 7219717 | TAGE G2 2R L13 90° 840 DALI | 84 | 10170 - 13500 | 4000 | 1456x95x52 | Stainless steel | IP23 |
| 7219730 | TAGE G2 L16 30° 840 | 76 | 9300 - 12100 | 4000 | 1736x95x42 | Stainless steel | IP23 |
| 7219732 | TAGE G2 L16 60° 840 | 76 | 9000 - 11800 | 4000 | 1736x95x42 | Stainless steel | IP23 |
| 7219738 | TAGE G2 L16 90° 840 | 76 | 9180 - 12000 | 4000 | 1736x95x42 | Stainless steel | IP23 |
| 7219740 | TAGE G2 L16 30° 840 DALI | 76 | 9300 - 12100 | 4000 | 1736x95x42 | Stainless steel | IP23 |
| 7219741 | TAGE G2 L16 60° 840 DALI | 76 | 9000 - 11800 | 4000 | 1736x95x42 | Stainless steel | IP23 |
| 7219746 | TAGE G2 L16 90° 840 DALI | 76 | 9180 - 12000 | 4000 | 1736x95x42 | Stainless steel | IP23 |
| 7219757 | TAGE G2 2R L16 30° 840 | 105 | 14600 - 17300 | 4000 | 1736x95x52 | Stainless steel | IP23 |
| 7219758 | TAGE G2 2R L16 60° 840 | 105 | 14000 - 16600 | 4000 | 1736x95x52 | Stainless steel | IP23 |
| 7219759 | TAGE G2 2R L16 90° 840 | 105 | 14200 - 16900 | 4000 | 1736x95x52 | Stainless steel | IP23 |
| 7219765 | TAGE G2 2R L16 30° 840 DALI | 105 | 14600 - 17300 | 4000 | 1736x95x52 | Stainless steel | IP23 |
| 7219766 | TAGE G2 2R L16 60° 840 DALI | 105 | 14000 - 16600 | 4000 | 1736x95x52 | Stainless steel | IP23 |
| 7219767 | TAGE G2 2R L16 90° 840 DALI | 105 | 14200 - 16900 | 4000 | 1736x95x52 | Stainless steel | IP23 |
| 7219776 | TAGE G2 L13 60° 840 Q | 59 | 7000 - 9100 | 4000 | 1456x95x42 | Stainless steel | IP23 |
| 7219777 | TAGE G2 L13 90° 840 Q | 59 | 7100 - 9270 | 4000 | 1456x95x42 | Stainless steel | IP23 |
| 7219778 | TAGE G2 L13 60° 840 DALI Q | 59 | 7000 - 9100 | 4000 | 1456x95x42 | Stainless steel | IP23 |
| 7219779 | TAGE G2 L13 90° 840 DALI Q | 59 | 7100 - 9270 | 4000 | 1456x95x42 | Stainless steel | IP23 |
| 7219787 | TAGE G2 2R L13 60° 840 Q | 84 | 10000 - 13300 | 4000 | 1456x95x52 | Stainless steel | IP23 |
| 7219788 | TAGE G2 2R L13 90° 840 Q | 84 | 10170 - 13500 | 4000 | 1456x95x52 | Stainless steel | IP23 |
| 7219789 | TAGE G2 2R L13 60° 840 DALI Q | 84 | 10000 - 13300 | 4000 | 1456x95x52 | Stainless steel | IP23 |
| 7219790 | TAGE G2 2R L13 90° 840 DALI Q | 84 | 10170 - 13500 | 4000 | 1456x95x52 | Stainless steel | IP23 |
| 7219795 | TAGE G2 L16 30° 840 Q | 76 | 9300 - 12100 | 4000 | 1736x95x42 | Stainless steel | IP23 |
| 7219796 | TAGE G2 L16 60° 840 Q | 76 | 9000 - 11800 | 4000 | 1736x95x42 | Stainless steel | IP23 |
| 7219797 | TAGE G2 L16 90° 840 Q | 76 | 9180 - 12000 | 4000 | 1736x95x42 | Stainless steel | IP23 |
| 7219798 | TAGE G2 L16 30° 840 DALI Q | 76 | 9300 - 12100 | 4000 | 1736x95x42 | Stainless steel | IP23 |
| 7219799 | TAGE G2 L16 60° 840 DALI Q | 76 | 9000 - 11800 | 4000 | 1736x95x42 | Stainless steel | IP23 |
| 7219800 | TAGE G2 L16 90° 840 DALI Q | 76 | 9180 - 12000 | 4000 | 1736x95x42 | Stainless steel | IP23 |
| 7219842 | TAGE G2 2R L16 30° 840 Q | 105 | 14600 - 17300 | 4000 | 1736x95x52 | Stainless steel | IP23 |
| 7219843 | TAGE G2 2R L16 60° 840 Q | 105 | 14000 - 16600 | 4000 | 1736x95x52 | Stainless steel | IP23 |
| 7219890 | TAGE G2 2R L16 90° 840 Q | 105 | 14200 - 16900 | 4000 | 1736x95x52 | Stainless steel | IP23 |
| 7219891 | TAGE G2 2R L16 30° 840 DALI Q | 105 | 14600 - 17300 | 4000 | 1736x95x52 | Stainless steel | IP23 |
| 7219892 | TAGE G2 2R L16 60° 840 DALI Q | 105 | 14000 - 16600 | 4000 | 1736x95x52 | Stainless steel | IP23 |
| 7219893 | TAGE G2 2R L16 90° 840 DALI Q | 105 | 14200 - 16900 | 4000 | 1736x95x52 | Stainless steel | IP23 |