Isa

https://exaktor.com/en/product/isa/

2026-11-14





- Dimmable ceiling light IP54 with up and down light
- Adjustable colour temperature
- Adjustable with several accessories



A stylish and versatile ceiling light available in two sizes, with adjustable colour temperature and brightness. The combination of downlight and uplight provides a pleasant and even light distribution.

The luminaire is mounted directly on the wall or ceiling and is suitable for corridors, stairwells, storage rooms, toilets, basements, changing rooms and other public areas. Can also be used as pendant lighting in areas with slightly higher ceilings with the help of accessories.

The luminaire is D-marked according to SS-EN 60598-2-24 and may be placed in areas with an increased fire risk.

Isa is available in on/off versions, with a microwave sensor (RS) and as a BTDA version with an app-controlled RS sensor via the Exaktor Koolmesh app.

A decorative ring with microprismatic film is available as an accessory for reduced glare and a softer light pattern. For flexible mounting, a 1.5 m wire suspension kit, as well as a ceiling cup and suspension arm 0.3–0.6 m, are also available as accessories.

Variations

E-number	Product name	Max. system power (W)	Colour temperature (K)	Beam angle (°)	Mått (DxH/D, mm)	Colour	IK class
7029194	Isa 280 DIM 3-4K	20	3000 - 4000	110	280x55	White	IK08
7029195	Isa 280 DALI 3-4K	20	3000 - 4000	110	280x55	White	IK08
7029196	Isa 280 RS DIM 3-4K	20	3000 - 4000	110	280x55	White	IK08
7511170	ISA 400 DIM 3-4K	32	3000 - 4000	110	400x60	White	IK08
7511171	ISA 400 DALI 3-4K	32	3000 - 4000	110	400x60	White	IK08
7511172	ISA 400 RS DIM 3-4K	32	3000 - 4000	110	400x60	White	IK08