

INDO L18 MP 830/840 FLEX

E-number: 7220292

Description

Barcode:	7330139296368
Series:	Indo

Photometric data

Rated luminous flux (lm):	15140
Max. system power (W):	139
Light source:	LED exchangeable
Lamp holder:	Other
Light source included:	Yes
Min colour temperature (K):	3000
Max colour temperature (K):	4000
Colour rendering index CRI:	80-89
Colour consistency:	SDCM3
Beam angle (°):	80
Light sharing:	Symmetric
Light distributor:	Diffuser lens/optic/panel
Light outlet:	Direct
Lumen median 35000h (tq):	94
Lumen median 50000h (tq):	94
Lumen median 75000h (tq):	91
Lumen median 100000h (tq):	88
Failure rate median 35000h:	6
Failure rate median 50000h:	6
Failure rate median 75000h:	91
Failure rate median 100000h:	12
Meets min. EIA service life:	Ja
Flickering value Pst LM:	0.02
Energy efficiency class:	B

Technical data

Spänning, nominell (V):	230
Min nominal voltage (V):	220
Max nominal voltage (V):	240
Voltage type:	AC
Type of control gear:	LED operating device current-controlled
With control gear:	Yes
Min nominal current (mA):	800
Max nominal voltage (V):	240
Power factor:	0.98

Control

Operation by Bluetooth:	No
With movement sensor:	Nej

Materials and environmental data

Housing material:	Aluminium
Housing colour:	Aluminium
Material cover:	Plastic, transparent
Country of origin:	CN
Surface protection housing:	Anodiserad/Eloxerad

Connection and installation

Protection class:	I
Impact strength (IK):	IK08
Suitable surface mounting:	Yes
Suitable suspended mounting:	Yes
Min ambient temperature:	-20
Max ambient temperature:	45
Type of wiring:	Through wiring included
Fuse B16 (st):	10
Fuse C16 (st):	16

Dimensions and weight

Length (mm):	1822
Width (mm):	75
Height/depth (mm):	70
Weight armature (kg):	5.03
Length/depth package (mm):	1832
Width package (mm):	85
Height package (mm):	80
Weight package (kg):	5.39
Number in FP:	1

Number per pallet:

48



Do you need support?

offert@exaktor.se

0370-69 07 20

exaktor.com/en

exaktor