

# INDO L18 60° 830/840 DALI

E-number: 7220301

## Description

Barcode:	7330139296450
Series:	Indo

## Photometric data

Rated luminous flux (lm):	16880
Max. system power (W):	119
Light source:	LED exchangeable
Lamp holder:	Other
Light source included:	Yes
Min colour temperature (K):	3000
Max colour temperature (K):	4000
Colour rendering index CRI:	80-89
Colour consistency:	SDCM3
Beam angle (°):	60
Light sharing:	Symmetric
Light distributor:	Diffuser lens/optic/panel
Light outlet:	Direct
Lumen median 35000h (tq):	94
Lumen median 50000h (tq):	94
Lumen median 75000h (tq):	91
Lumen median 100000h (tq):	88
Failure rate median 35000h:	6
Failure rate median 50000h:	6
Failure rate median 75000h:	91
Failure rate median 100000h:	12
Meets min. EIA service life:	Ja

## Technical data

Spänning, nominell (V):	230
Min nominal voltage (V):	220
Max nominal voltage (V):	240
Voltage type:	AC
Type of control gear:	LED operating device current-controlled
With control gear:	Yes
Max nominal voltage (V):	240
Power factor:	0.95

## Control

Operation by Bluetooth:	No
Dimming DALI:	Yes
Dimming DALI-2:	Yes
With movement sensor:	Nej

## Materials and environmental data

Housing material:	Aluminium
Housing colour:	Aluminium
Material cover:	Plastic, transparent
Country of origin:	CN
Surface protection housing:	Anodiserad/Eloxerad

## Connection and installation

Protection class:	I
Suitable surface mounting:	Yes
Suitable suspended mounting:	Yes
Type of wiring:	Through wiring included
Fuse B16 (st):	15
Fuse C16 (st):	25

## Dimensions and weight

Length (mm):	1822
Width (mm):	75
Height/depth (mm):	70
Weight armature (kg):	5.03
Length/depth package (mm):	1832
Width package (mm):	85
Height package (mm):	80
Weight package (kg):	5.39
Number in FP:	1
Number per pallet:	48



Do you need support?

[offert@exaktor.se](mailto:offert@exaktor.se)

0370-69 07 20

[exaktor.com/en](http://exaktor.com/en)

exaktor