

- Pleasant glare-free light for maximum comfort
- Dimmable with adjustable output and color temperature
- High color rendering with CRI>90



Stylish downlight with white textured ring, matt reflector and lens-equipped LED. The luminaire provides excellent light distribution and glare control (UGR < 19). The series is available in three sizes: S, M and L. All models have adjustable colour temperature and CRI > 90 as standard. Suitable for environments with high demands on light quality, such as schools, offices, hotels and homes.

Available with phase dimming (front/rear edge) or DALI. The phase dimmable version has a 3-pole quick-connect terminal with bypass, while the DALI version has a 5-pole quick-connect terminal. A connector between the driver and the luminaire simplifies installation. The driver is equipped with screwless strain relief where 16 mm flexible hose can be locked without tools.

Variations

E-number	Product name	Max. system power (W)	Colour temperature (K)	Beam angle (°)	Mått (LxWxH/D, mm)	Colour	IK class
7478203	Uma S 36° TILT 3CCT W DIM	10	2700 - 4000	36	-x-x54	White	IK06
7478204	Uma S 36° TILT 3CCT W DALI	10	2700 - 4000	36	-x-x54	White	IK06
7478215	Uma M 36° 3CCT W DIM	25	3000 - 5000	36	-x-x90	White	IK06
7478216	Uma M 36° 3CCT W DALI	25	3000 - 5000	36	-x-x90	White	IK06
7478221	Uma L 36° 3CCT W DIM	30	3000 - 5000	36	-x-x99	White	IK06
7478222	Uma L 36° 3CCT W DALI	30	3000 - 5000	36	-x-x99	White	IK06