




- Ceiling light (IP54) with adjustable color temperature
- With integrated BTDA sensor for control via Koolmesh
- Adjustable with several accessories



A stylish and versatile ceiling light available in two sizes, with adjustable colour temperature. The combination of downlight and uplight provides a pleasant and even light distribution.

The luminaire is mounted directly on the wall or ceiling and is suitable for corridors, stairwells, storage rooms, toilets, basements, changing rooms and other public areas. Can also be used as pendant lighting in areas with slightly higher ceilings with the help of accessories.

The luminaire is D-marked according to SS-EN 60598-2-24 and may be placed in areas with an increased fire risk.

Do you need support?

offert@exaktor.se

0370-69 07 20

exaktor.com/en

Variations

E-number	Product name	Max. system power (W)	Lumen (lm)	Colour temperature (K)	Beam angle (°)	Mått (LxWxH/D, mm)	Colour
7029198	Isa 280 BTDA RS 3-4K	20		3000 - 4000	110	-x-x55	White
7029199	Isa 280 BTDA PIR 3-4K	20		3000 - 4000	110	-x-x55	White
7511174	ISA 400 BTDA RS 3-4K	32	2900 - 4500	3000 - 4000	110	-x-x60	White
7511175	ISA 400 BTDA PIR 3-4K	32		3000 - 4000	110	-x-x60	White