

- Always with through wire and internal quick-connector
- HACCP compliant with EU 852/2004
- Availabe as On/Off or DALI

Mamba HACCP is a robust luminaire with IP66 and IK08 ratings, developed for environments where there are high demands on hygiene, safety and durability. It is specifically designed for use in the food industry and is well suited to production and processing environments. The luminaire is fire-rated to UL94 V-2 and complies with the requirements of the food industry's international standard (EU) No 852/2004 (HACCP).

Mamba HACCP is available in two lengths, 1200 mm and 1500 mm, and is available as On/Off or with DALI. The luminaire has a colour temperature of 4000 K and is available with a beam angle of 90° or 120°, making it possible to adapt the light distribution to suit different types of installations.

The luminaire features a bypass connection and is easy to install thanks to the quick-connect system between the housing and the LEDs.

Variations

E-number	Product name	Max. system power (W)	Lumen (lm)	Colour temperature (K)	Beam angle (°)	Mått (LxWxH/D, mm)	Colour
7221613	MAMBA HACCP L12 90° 4K	44	4100 - 6900	4000	90	1282x100x84	Grey
7221614	MAMBA HACCP L12 90° 4K DA	44	4100 - 6900	4000	90	1282x100x84	Grey
7221615	MAMBA HACCP L12 120° 4K	44	4000 - 6800	4000	120	1282x100x84	Grey
7221616	MAMBA HACCP L12 120° 4K DA	44	4000 - 6800	4000	120	1282x100x84	Grey
7221617	MAMBA HACCP L15 90° 4K	53	5000 - 8400	4000	90	1578x100x84	Grey
7221618	MAMBA HACCP L15 90° 4K DA	53	5000 - 8400	4000	90	1578x100x84	Grey
7221619	MAMBA HACCP L15 120° 4K	53	4900 - 8300	4000	120	1578x100x84	Grey
7221620	MAMBA HACCP L15 120° 4K DA	53	4900 - 8300	4000	120	1578x100x84	Grey