



- Several different optics
- Optimal glare and light scattering



exStreet is a post top luminaire with optimal glare control and light distribution that will provide a safer and improved light environment for pedestrians, cyclists and motorists when it is dark. The luminaire is suitable as lighting for, for example, streets, roads, electric light tracks, footpaths, cycle paths, parks and parking lots. The luminaire is available with several different optics and effects, making it possible to adapt the light to the environment to be illuminated. Recommended installation heights: 15W 3-7 m / 30W 3-8 m / 50W 6-10 m. exStreet has a built-in driver with 6kV surge protection and an additional 10kV SPD (Surge Protection Device) to protect against lightning strikes. The luminaire is mounted on the top of a pole or on a pole arm. The standard screws supplied with the luminaire are suitable for Ø 60-66mm pole/arm mounting but there are longer screws available for 48mm diameter trunks, which must be specified when ordering. The mounting angle can easily be adjusted +/- 15° with the included bracket. exStreet Mini is delivered as standard with 7.0m 3x1.5mm<sup>2</sup> rubber cable. exStreet 30W and exStreet 50W are delivered as standard with 10.0m 3x1.5mm<sup>2</sup> rubber cable. On request it is possible to order exStreet with adjusted power and a number of light control options such as DALI, CLO and Astro or timer based night dimming/night switching (night dimming/night switching requires an external twilight relay or astro clock).

Do you need support?

[offert@exaktor.se](mailto:offert@exaktor.se)

0370-69 07 20

[exaktor.com/en](https://exaktor.com/en)

## Variations

E-number	Product name	Max. system power (W)	Colour temperature (K)	Mått (LxWxH/D, mm)	Colour	IK class	Ambient temperature (°C)
7727461	exStreet 30/740 O1 Grå	30	4000	680x282x160	Grey	IK08	-30 - 50
7727462	exStreet 30/740 O2 Grå	30	4000	680x282x160	Grey	IK08	-30 - 50
7727463	exStreet 30/740 O3 Grå	30	4000	680x282x160	Grey	IK08	-30 - 50
7727464	exStreet 50/740 O1 Grå	50	4000	680x282x160	Grey	IK08	-30 - 50
7727465	exStreet 50/740 O2 Grå	50	4000	680x282x160	Grey	IK08	-30 - 50
7727466	exStreet 50/740 O3 Grå	50	4000	680x282x160	Grey	IK08	-30 - 50
7727617	exStreet mini 15/740 O4	15	4000	613x222x159	Grey	IK08	-30 - 50
7727618	exStreet mini 15/740 O5	15	4000	613x222x159	Grey	IK08	-30 - 50
7727750	exStreet mini 15/740 O2	15	4000	613x222x159	Grey	IK08	-30 - 50
7727751	exStreet 30/740 O4 Grå	30	4000	680x282x160	Grey	IK08	-30 - 50
7727752	exStreet 30/740 O5 Grå	30	4000	680x282x160	Grey	IK08	-30 - 50
7727753	exStreet 50/740 O4 Grå	50	4000	680x282x160	Grey	IK08	-30 - 50
7727754	exStreet 50/740 O5 Grå	50	4000	680x282x160	Grey	IK08	-30 - 50