



- Two sizes with effective light scattering
- Available with different controls
- Available with Dusk to Dawn



exWall is a facade luminaire in die-cast aluminum for industrial buildings and other properties. The luminaire has an asymmetrical light pattern with pleasant light and effective light distribution. exWall is equipped with surge protection 6kV that protects against lightning strikes. On the back of the mounting box is a gasket that reduces the pressure of the luminaire against the wall, it also prevents water from entering the luminaire when the cable is inserted from the back. The luminaire is easy to clean if necessary. The luminaire is available with several different light control options, 4000K and in the colors black or bronze. exWall on/off exWall Flex has adjustable power and luminous flux, which the installer can do on site by a simple rewiring of the actuator. Adjustable modes for power / luminous flux are: 33W, 4300 lm (700mA) 24W, 3200 lm (500mA) 17W, 2300 lm (350mA) exWall DALI has CLO (Constant Light Output) as standard for additional energy savings. exWall D2D has CLO (Constant Light Output) as standard for additional energy savings. The night-time dimming is pre-programmed and starts automatically when the property's light relay/timer turns on the power to the luminaire, no further programming is required. As standard, the luminaire is delivered with a programming that allows the luminaire to dim to 50% between 22:00 - 04:00. On request, the programming can be customized with times and light level. On request, exWall can be supplemented with a connection cable.

Do you need support?offert@exaktor.se

0370-69 07 20

exaktor.com/en

Variations

| E-number | Product name | Max. system power (W) | Lumen (lm) | Colour temperature (K) | Mått (LxWxH/D, mm) | Colour | IP-class |
|----------|----------------------------|-----------------------|-------------|------------------------|--------------------|--------|----------|
| 7703400 | exWall 40 840 Svart/Brons | 40 | 5200 | 4000 | 296x223x150 | Brown | IP65 |
| 7703761 | exWall 40 840 Svart | 40 | 5200 | 4000 | 296x223x150 | Black | IP65 |
| 7704306 | exWall Flex 840 Svart | 33 | 4300 | 4000 | 296x223x150 | Black | IP65 |
| 7704307 | exWall Flex 840 Brons | 33 | 4300 | 4000 | 296x223x150 | Bronze | IP65 |
| 7706119 | exWall SV 840 DALI | 36 | 4300 | 4000 | 296x223x150 | Black | IP65 |
| 7706120 | exWall BR 840 DALI | 36 | 4300 | 4000 | 296x223x150 | Brown | IP65 |
| 7706121 | exWall SV 840 D2D NATTSÄNK | 36 | 4300 | 4000 | 296x223x150 | Black | IP65 |
| 7706122 | exWall BR 840 D2D NATTSÄNK | 36 | 4300 | 4000 | 296x223x150 | Brown | IP65 |
| 7706625 | exWall S FLEX SVART | 20 | 1300 - 2600 | 3000 - 4000 | 200x110x180 | Black | IP66 |