

Description

Barcode:7330139295460, 7330139295002, 7330139295279, 7330139295286, 7330139295293, 7330139295309, 7330139295316, 7330139295323, 7330139295330

Series: exWall

Photometric data

Rated luminous flux (lm):	4300, 2600, 5200
Min luminous flux (lm):	1300, 2061, 4300
Max luminous flux (lm):	2600, 4300, 5200
Luminaire efficacy (lm/W):	130, 119
Max. system power (W):	0, 36, 33, 40
Light source:	LED exchangeable
Light source included:	Yes
Min colour temperature (K):	4000, 3000
Max colour temperature (K):	4000
Colour rendering index CRI:	80-89
Colour consistency:	SDCM3, SDCM5
Light sharing:	Asymmetric
Light distributor:	Focal lens
Light outlet:	Direct
Lumen median 50000h (tq):	90, 92
Lumen median 75000h (tq):	86, 85
Lumen median 100000h (tq):	80, 84
Failure rate median 75000h:	86, 85
Flickering value Pst LM:	1
Energy efficiency class:	D

Technical data

Spänning, nominell (V):	230
Min nominal voltage (V):	220, 100
Max nominal voltage (V):	240
Voltage type:	AC
Frequency (Hz):	50, 0
Type of control gear:	LED operating device current-controlled
With control gear:	Yes
Control gear manufacturer:	SELV, Constant Current
Min nominal current (mA):	900, 80
Max nominal voltage (V):	240
Constant light output (CLO):	Yes
Power factor:	0.88, 0.9

Control

Operation by Bluetooth:	No
Dimming DALI-2:	Yes
With movement sensor:	False

Materials and environmental data

Housing material:	Aluminium
Housing colour:	Black, Bronze, Brown
Material cover:	Without cover
Country of origin:	CN, SE
Surface protection housing:	Pulverlackerad

Connection and installation

Degree of protection (IP):	IP65, IP66
Protection class:	I
Impact strength (IK):	IK10
Suitable surface mounting:	Yes
Suitable for wall mounting:	Yes
Min ambient temperature:	-30
Max ambient temperature:	50
D-marked (EN 60598-2-24):	Yes
Type of wiring:	Suitable for through wiring
Fuse B10 (st):	13, 18, 46, 47
Fuse B16 (st):	30, 76, 23, 4
Fuse C10 (st):	22, 30, 46, 48
Fuse C16 (st):	51, 95, 36, 7

Dimensions and weight

Length (mm):	200, 296
Width (mm):	110, 223
Height/depth (mm):	150, 180
Weight armature (kg):	1.4, 3.9
Length/depth package (mm):	250, 272

Width package (mm):	200, 250
Height package (mm):	130, 350
Weight package (kg):	1.5, 4
Number in FP:	1
Number per pallet:	93



Do you need support?

offert@exaktor.se

0370-69 07 20

exaktor.com/en