



- Anti glare
- Made in Värnamo, Sweden



Hugin Pendant is based on a luminaire concept in two lengths; 1200 and 1500mm. Hugin is an efficient general lighting for e. g. offices, shops or schools that is suspended with the included 1.5m wire and reutlingen suspension. The luminaire is available in variants with on/off or DALI, 3000K or 4000K and in variants with HO (high luminous flux). On/off comes with a 3.0m cord with plug. DALI can be connected as DALI or as impulse control/switch dim and is delivered as standard with 3.0m 5-wire cable. On request, Hugin can be ordered with CRI 90, adapted luminous flux, rampable, emergency light, motion sensor or constant light control. In the same luminaire series, there is a suspended ceiling version and a recessed version. The luminaire is manufactured in Värnamo.

Variations

E-number	Product name	Max. system power (W)	Colour temperature (K)	Mått (LxWxH/D, mm)	Colour	IP-class	Ambient temperature (°C)
7020142	HUGIN L120 830	31	3000	1195x128x73	White	IP20	-20 - 35
7020143	HUGIN L120 840	31	4000	1195x128x73	White	IP20	-20 - 35
7020144	HUGIN L120 830 HO	54	3000	1195x128x73	White	IP20	-20 - 35
7020145	HUGIN L120 840 HO	54	4000	1195x128x73	White	IP20	-20 - 35
7020146	HUGIN L120 830 DALI	31	3000	1195x128x73	White	IP20	-20 - 35
7020147	HUGIN L120 840 DALI	31	4000	1195x128x73	White	IP20	-20 - 35
7020148	HUGIN L150 830	50	3000	1481x128x73	White	IP20	-20 - 35
7020149	HUGIN L150 840	50	4000	1481x128x73	White	IP20	-20 - 35
7020150	HUGIN L150 830 HO	70	3000	1481x128x73	White	IP20	-20 - 35
7020151	HUGIN L150 840 HO	70	4000	1481x128x73	White	IP20	-20 - 35
7020152	HUGIN L150 830 DALI	50	3000	1481x128x73	White	IP20	-20 - 35
7020153	HUGIN L150 840 DALI	50	4000	1481x128x73	White	IP20	-20 - 35