

- Fulfills the requirements for D-marking
- Made in Värnamo, Sweden



Mamba LED is a durable luminaire suitable for demanding environments, such as industries, carpentry and animal housing. The luminaire meets the requirements for D-labeling, is available in three different lengths (600, 1200 or 1500mm), with different light control options and with or without ballast (ÖK). On/off DALIRS is equipped with a motion sensor that switches the luminaire on in case of presence and off if no presence is registered during the set delay time (5min). The sensor can be sensitive to vibrations, valve trions and the like, which means that it can detect errors. It is possible to let an RS luminaire operate luminaires without RS. However, a maximum of five slave luminaires per RS luminaire. Mamba LED RS is best suited for ceiling heights up to 4m. On request, Mamba LED can be supplied with Bluetooth communication for wireless routing and grouping of luminaires. The luminaire is manufactured in Värnamo.



Variations

E-number	Product name	Max. system power (W)	Lumen (Im)	Colour temperature (K)	Mått (LxWxH/D, mm)	Colour	IP-class
7223569	MAMBA L60/840/449	36		4000	1276×170×108	Grey	IP65
7223576	MAMBA L60/840/449 DALI	36		4000	1276×170×108	Grey	IP65
7223660	MAMBA L72/840/449	53	7500	4000	1576x170x108	Grey	IP65
7223661	MAMBA L72/840/449 RS	53	7500	4000	1576×170×108	Grey	IP65
7223662	MAMBA L72/840/449 DALI	53	7500	4000	1576x170x108	Grey	IP65
7223548	MAMBA L30/840/449 RS	18		4000	666x170x108	Grey	IP65
7223549	MAMBA L60/840/449 RS	36		4000	1276×170×108	Grey	IP65
7223558	MAMBA L30/840/449	18			666x170x108	Grey	IP65
7211403	MAMBA LED 840 L666 ej ÖK	18	2061	4000	666x170x108	Grey	IP65
7211404	MAMBA LED 840 L1276 ej ÖK	36	4122	4000	1276x170x108	Grey	IP65
7215944	MAMBA LED HO DALI 158 840	95	12000	4000	1576x170x108	Grey	IP65
7215945	MAMBA LED HO RS 158 840	95	12000	4000	1576×170×108	Grey	IP65
7215946	MAMBA LED HO RSDIM 158 840	95	12000	4000	1576x170x108	Grey	IP65
7215943	MAMBA LED HO 158 840	95	12000	4000	1576x170x108	Grey	IP65
7223559	MAMBA L30/840/449 DALI	18		4000	666x170x108	Grey	IP65
7211405	MAMBA LED 840 L1576 ei ÖK	53	7500	4000	1576x170x108	Grev	IP65

