MAMBA LED

https://exaktor.com/en/product/mamba-led/

2026-11-22



- Fulfills the requirements for D-marking
- Made in Värnamo, Sweden

IP65

Mamba LED is a durable luminaire suitable for demanding environments, such as industries, carpentry and animal housing. The luminaire meets the requirements for D-labeling, is available in three different lengths (600, 1200 or 1500mm), with different light control options and with or without ballast (ÖK). On/off DALIRS is equipped with a motion sensor that switches the luminaire on in case of presence and off if no presence is registered during the set delay time (5min). The sensor can be sensitive to vibrations, valve trions and the like, which means that it can detect errors. It is possible to let an RS luminaire operate luminaires without RS. However, a maximum of five secondary luminaires per RS luminaire. Mamba LED RS is best suited for ceiling heights up to 4m. On request, Mamba LED can be supplied with Bluetooth communication for wireless routing and grouping of luminaires. The luminaire is manufactured in Värnamo.

Variations

E-number	Product name	Max. system power (W)	Lumen (lm)	Colour temperature (K)	Mått (LxWxH/D, mm)	Colour	IK class
7223558	MAMBA L30/840/449	18			666x170x108	Grey	IK03
7223569	MAMBA L60/840/449	36		4000	1276x170x108	Grey	IK03
7223660	MAMBA L72/840/449	53	7500	4000	1576x170x108	Grey	IK03