

- Fulfills the requirements for D-marking
- Made in Värnamo, Sweden



Mamba Mini is an IP66 rated luminaire for indoor or outdoor environments under protection, such as industry, workshop, garage, culvert or basement. The luminaire is fire rated (UL94):V2 and meets the food industry's international standard; (EU) No. 852/2004 (HACCP). The luminaire is available in two different lengths (1200 or 1500mm), with 4000K, in three different product variants (BAS, MID or PRO) and as on/off or DALI. Mamba Mini Agro in 1500 length with DALI is also available in a variant with high luminous flux (HO). On/off DALI can be connected as DALI or as impulse control/Switch Dim. BAS: 1 x 3 pole terminal for 1-phase connection at the side. MID: 2 x 5 pole terminals for 3-phase switching with 5x2. 5 mm² cables. PRO: 2 x 5 pole terminals for 3-phase switching with 5x2. 5 mm² wires. PRO DALI: 2 x 5 pole terminals for 1-phase and DALI over-connection with 5x2. 5 mm² wires. The luminaire is manufactured in Värnamo.

Variations

E-number	Product name	Max. system power (W)	Lumen (lm)	Colour temperature (K)	Mått (LxWxH/D, mm)	Colour	IP-class
7211568	MAMBAmMini BAS L1277 840	24	3100	4000	1277x104x84	Grey	IP66
7211569	MAMBAmMini MID L1277 840	26	3100	4000	1277x104x84	Grey	IP66
7211570	MAMBAmMini PRO L1277 840	36	5000	4000	1277x104x84	Grey	IP66
7211571	MAMBAmMini PRO DALI L1277 840	36	5000	4000	1277x104x84	Grey	IP66
7212056	MAMBAmMini BAS L1573 840	30	3900	4000	1573x104x84	Grey	IP66
7212057	MAMBAmMini MID L1573 840	28	3900	4000	1573x104x84	Grey	IP66
7212058	MAMBAmMini PRO L1573 840	48	6300	4000	1573x104x84	Grey	IP66
7212059	MAMBAmMini PRO DALI L1573 840	48	6300	4000	1573x104x84	Grey	IP66
7214354	MAMBAmMini HO L1573 840	63	8000	4000	1573x104x84	Grey	IP66
7214355	MAMBAmMini HO DALI L1573 840	63	8000	4000	1573x104x84	Grey	IP66
7214673	MAMBAmMID L1277 840 RS	26	3100	4000	1277x104x84	Grey	IP66
7214674	MAMBAmMID PRO L1277 840 RS	36	5000	4000	1277x104x84	Grey	IP66
7214675	MAMBAmMID PRO L1277 840 RSDIM	36	5000	4000	1277x104x84	Grey	IP66
7214676	MAMBAmMID L1573 840 RS	28	3890	4000	1578x104x84	Grey	IP66
7214677	MAMBAmMID PRO L1573 840 RS	48	6340	4000	1578x104x84	Grey	IP66
7214678	MAMBAmMID PRO L1573 840 RSDIM	48	6340	4000	1578x104x84	Grey	IP66
7214683	MAMBAmHO L1573 840 RS	63	8000	4000	1578x104x84	Grey	IP66
7214684	MAMBAmHO L1573 840 RSDIM	63	8000	4000	1578x104x84	Grey	IP66
7215579	MAMBAmMID PRO L1277 840 BTDA	36	5000	4000	1277x104x84	Grey	IP66
7215580	MAMBAmMID PRO L1573 840 BTDA	48	6340	4000	1578x104x84	Grey	IP66