



- Visual comfort
- CRI90 as standard



Lyra is a highly glare-free downlight for offices and other public environments. The luminaire has a metal frame and protection class II. Lyra can also be used in damp areas as it is IP44 from below. Lyra is available in three sizes 3, 6 and 8 with hole sizes 3 = 95-100mm, 6 = 165-180mm and 8 205-220mm. The luminaire is available in 3000K or 4000K and has an excellent color rendering CRI>90. The luminaire is available in variants with on/off or DALI. On/off is delivered with a free-standing strain relief actuator and 2.5m cord set. DALI can be connected as DALI or as impulse control/switch dim (for impulse control, all drivers must be of the same make). The DALI variant is supplied with a free-standing, strain-relieved DALI driver and 3.0m 5-wire cable.

## Variations

E-number	Product name	Max. system power (W)	Lumen (lm)	Colour temperature (K)	Mått (LxWxH/D, mm)	Colour	Ambient temperature (°C)
7470633	LYRA 3" 930	11	1000	3000	-x-x100	Grey	-20 - 45
7470634	LYRA 3" 930 DALI	16	1400	3000	-x-x100	Grey	-20 - 45
7470635	LYRA 3" 940	11	1000	4000	-x-x100	Grey	-20 - 45
7470636	LYRA 3" 940 DALI	16	1400	4000	-x-x100	Grey	-20 - 45
7470637	LYRA 6" 930	14	1400	3000	-x-x127	Grey	-20 - 45
7470638	LYRA 6" 930 DALI	14	1400	3000	-x-x127	Grey	-20 - 45
7470639	LYRA 6" 940	14	1400	4000	-x-x127	Grey	-20 - 45
7470640	LYRA 6" 940 DALI	14	1400	4000	-x-x127	Grey	-20 - 45
7470641	LYRA 8" 930	20	2000	3000	-x-x140	Grey	-20 - 45
7470642	LYRA 8" 930 DALI	20	2000	3000	-x-x140	Grey	-20 - 45
7470643	LYRA 8" 940	20	2000	4000	-x-x140	Grey	-20 - 45
7470644	LYRA 8" 940 DALI	20	2000	4000	-x-x140	Grey	-20 - 45