

- Both recessed and ceiling mounting
- Adjustable wattage and color temperature
- Available with built-in PIR sensor













With the Skir thin ceiling light, you can choose between three different color temperatures and three different effects – in the same luminaire. All you need to do is a simple adjustment on the back of the luminaire before installation. Skir is available in two sizes, 300 mm and 235 mm and in three different control variants, on/off, dimmable or with PIR sensor. Installation is simple and flexible; surface mounted or recessed with adjustable hole pattern. Protection class IP44 from below when mounted on a thick ceiling and IP20 when mounted with spacers. Skir Dim can be dimmed with front or rear edge dimmer (phase cut dimmer). Adjustable modes for power/luminous flux (at 4000K) for the on/off variant of Skir 300:16W, 1860 Im20W, 2240 Im22W, 2420 ImAdjustable power/luminous flux modes (at 4000K) for the on/off variant of Skir 235:8W, 900 Im10W, 1100 Im12W, 1300 ImSkir PIR is ideal for lighting in stairwells, corridors and other areas where many people are in motion. Presence detection with adjustable infrared sensor (PIR) provides high precision and reduces the risk of false detection. The sensor on Skir has several setting options. You can set the detection area size, detection hold time, light sensor, ambient light and ambient light time. Adjustable modes for Skir PIR power / luminous flux (at 4000K)10W, 1233 Im15W, 1804 Im20W, 2317 Im



Variations

| E-number | Product name | Max. system power (W) | Lumen (Im) | Colour temperature (K) | Beam angle (°) | Mått (LxWxH/D, mm) | Colour |
|----------|---------------------------|-----------------------|-------------|------------------------|----------------|--------------------|--------|
| 7509113 | SKIR 235MM 8-12W 3-5.7K | 12 | 900 - 1300 | 3000 - 5700 | 120 | -x-x22 | White |
| 7509114 | SKIR 235MM 12W DIM 3-5.7K | 12 | 1300 | 3000 - 5700 | 120 | -x-x22 | White |
| 7510496 | SKIR PIR 10-20W 3-5.7K | 20 | 1200 - 2300 | 3000 - 5700 | 120 | -x-x25 | White |
| 7519655 | SKIR 300MM 10-20W 3-5.7K | 20 | 1100 - 2300 | 3000 - 5700 | 120 | -x-x25 | White |
| 7519656 | SKIR 300MM 22W DIM 3-5.7K | 22 | 2400 | 3000 - 5700 | 120 | -x-x25 | White |
| 7028194 | SKIR PIR 8-12W 3-5,7K | 12 | 700 - 1300 | 3000 - 5700 | 120 | -x-x22 | White |

