



- Stylish and functional pendant lighting
- Prismatic glare shield or reflector glare shield
- Made in Värnamo, Sweden



Stratus is a stylish and functional pendant interior luminaire for offices, conference rooms or schools. The luminaire has a wide-spreading uplight (55% on the 1200 variant and 60% on the 1500 variant) and a well-glare downlight (45% on the 1200 variant and 40% on the 1500 variant) towards the work surface, which makes the luminaire suitable for environments with high demands on glare. Stratus is available in two different lengths (1200 and 1500mm), in 3000 and 4000K and with microprismatic glare control or reflector glare control. The luminaire is available with the following controls: DALI can be connected as DALI or as impulse control/Switch dim. Supplied with 3m 5-wire cable as standard. DE Direct/indirect light is jointly adjusted with a pull cord. Supplied with 3m cord set as standard. 2xDE Separate control of direct/indirect light with double pull dimmers. Supplied with 3m cord holder as standard. DE NS Direct/indirect light is jointly adjusted with a pull cord. Presence sensor which has a basic setting with a 15 minute hold time before it switches off. Upon ignition, it returns to the last used setting. This provides an energy-efficient and user-friendly solution that is appreciated by users who often return to the same workplace. Supplied with a 3m cord set as standard. 2xDE NS Separate control of direct/indirect light with double pull dimming. Presence sensor that has a basic setting with a hold time of 15 minutes before switching off. Upon ignition, it returns to the last used setting. This provides an energy-efficient and user-friendly solution that is appreciated by users who often return to the same workplace. Supplied with a 3m cord holder as standard. On request, Stratus can be ramp mounted with up to 10 luminaires in a row and ordered with different luminous flux. The luminaire is manufactured in Värnamo.

Variations

E-number	Product name	Max. system power (W)	Colour temperature (K)	Beam angle (°)	Mått (LxWxH/D, mm)	Colour	IK class
7013273	STRATUS L1200 840 P 2xDE	49	4000		1190x71x72	White	IK04
7013274	STRATUS L1200 830 P 2xDE	49	3000		1190x71x72	White	IK04
7013275	STRATUS L1200 840 R 2xDE	49	4000		1190x71x72	White	IK06
7013276	STRATUS L1200 830 R 2xDE	49	3000		1190x71x72	White	IK06
7015182	STRATUS L1200 840 P DA	47	4000		1190x71x72	White	IK04
7015183	STRATUS L1200 830 P DA	47	3000		1190x71x72	White	IK04
7015184	STRATUS L1200 840 R DA	47	4000		1190x71x72	White	IK06
7015185	STRATUS L1200 830 R DA	47	3000		1190x71x72	White	IK06
7015186	STRATUS L1200 840 P DE	47	4000		1190x71x72	White	IK04
7015187	STRATUS L1200 830 P DE	47	3000		1190x71x72	White	IK04
7015188	STRATUS L1200 840 R DE	47	4000		1190x71x72	White	IK06
7015189	STRATUS L1200 830 R DE	47	3000		1190x71x72	White	IK06
7026642	STRATUS L120 830 P DE NS	47	3000		1190x71x77	White	IK04
7026643	STRATUS L120 840 P DE NS	47	4000		1190x71x77	White	IK04
7026644	STRATUS L120 830 R DE NS	47	3000		1190x71x77	White	IK06
7026645	STRATUS L120 840 R DE NS	47	4000		1190x71x77	White	IK06
7026646	STRATUS L120 830 P 2xDE NS	47	3000		1190x71x77	White	IK04
7026647	STRATUS L120 840 P 2xDE NS	49	4000		1190x71x77	White	IK04
7026648	STRATUS L120 830 R 2xDE NS	49	3000		1190x71x77	White	IK06
7026649	STRATUS L120 840 R 2xDE NS	49	4000		1190x71x77	White	IK06
7026650	STRATUS L150 830 P DE NS	57	3000		1470x71x77	White	IK04
7026651	STRATUS L150 840 P DE NS	57	4000		1470x71x77	White	IK04
7026652	STRATUS L150 830 R DE NS	57	3000		1470x71x77	White	IK06
7026653	STRATUS L150 840 R DE NS	57	4000		1470x71x77	White	IK06
7026654	STRATUS L150 830 P 2xDE NS	59	3000		1470x71x77	White	IK04
7026655	STRATUS L150 840 P 2xDE NS	59	4000		1470x71x77	White	IK04
7026656	STRATUS L150 830 R 2xDE NS	59	3000		1470x71x77	White	IK06
7026657	STRATUS L150 840 R 2xDE NS	59	4000		1470x71x77	White	IK06
7028303	STRATUS L12 3K P DE sv	43	3000	90	1190x71x72	Black	IK04
7028304	STRATUS L12 4K P DE sv	43	4000	90	1190x71x72	Black	IK04
7028305	STRATUS L15 4K P DE sv	55	4000	90	1470x71x72	Black	IK04