



- Several different optics
- Optimal glare and light scattering



exStreet is a post top luminaire with optimal glare control and light distribution that will provide a safer and improved light environment for pedestrians, cyclists and motorists when it is dark. The luminaire is suitable as lighting for, for example, streets, roads, electric light tracks, footpaths, cycle paths, parks and parking lots. The luminaire is available with several different optics and effects, making it possible to adapt the light to the environment to be illuminated. Recommended installation heights: 15W 3-7 m / 30W 3-8 m / 50W 6-10 m. exStreet has a built-in driver with 6kV surge protection and an additional 10kV SPD (Surge Protection Device) to protect against lightning strikes. The luminaire is mounted on the top of a pole or on a pole arm. The standard screws supplied with the luminaire are suitable for Ø 60-66mm pole/arm mounting but there are longer screws available for 48mm diameter trunks, which must be specified when ordering. The mounting angle can easily be adjusted +/- 15° with the included bracket.

(night dimming/night switching requires an external twilight relay or astro clock).

**Do you need support?**

[offert@exaktor.se](mailto:offert@exaktor.se)

0370-69 07 20

[exaktor.com/en](https://exaktor.com/en)

**exaktor**

Variations

E-number	Product name	Max. system power (W)	Colour temperature (K)	Mått (LxWxH/D, mm)	Colour	IP-class	IK class
7727461	exStreet 30/740 O1 Grå	30	4000	680x282x160	Grey	IP66	IK08
7727462	exStreet 30/740 O2 Grå	30	4000	680x282x160	Grey	IP66	IK08
7727463	exStreet 30/740 O3 Grå	30	4000	680x282x160	Grey	IP66	IK08
7727464	exStreet 50/740 O1 Grå	50	4000	680x282x160	Grey	IP66	IK08
7727465	exStreet 50/740 O2 Grå	50	4000	680x282x160	Grey	IP66	IK08
7727466	exStreet 50/740 O3 Grå	50	4000	680x282x160	Grey	IP66	IK08
7727617	exStreet mini 15/740 O4	15	4000	613x222x159	Grey	IP66	IK08
7727618	exStreet mini 15/740 O5	15	4000	613x222x159	Grey	IP66	IK08
7727750	exStreet mini 15/740 O2	15	4000	613x222x159	Grey	IP66	IK08
7727751	exStreet 30/740 O4 Grå	30	4000	680x282x160	Grey	IP66	IK08
7727752	exStreet 30/740 O5 Grå	30	4000	680x282x160	Grey	IP66	IK08
7727753	exStreet 50/740 O4 Grå	50	4000	680x282x160	Grey	IP66	IK08
7727754	exStreet 50/740 O5 Grå	50	4000	680x282x160	Grey	IP66	IK08