

- Anti glare
- Made in Värnamo, Sweden



The interior luminaire Hugin for installation on ceilings is based on a luminaire concept in two lengths; 1200 and 1500mm. Hugin DT is an efficient general lighting for offices, shops or schools, for example, which is mounted on the ceiling using keyholes. The luminaire is available in different variants, on/off or DALI, 3000K or 4000K and in variants with high luminous flux, HO.

On/off has a terminal for connection centrally in the luminaire. DALI can be connected as DALI or as impulse control/switch dim. The DALI variant is delivered as standard with 3.0m 5-wire cable.

On request, the luminaire can be supplied with CRI 90, adjusted luminous flux, override, emergency light, motion sensor or constant light control.

In the same luminaire series there is a pendant version and a recessed version.

The luminaire is manufactured in Värnamo.

Variations

E-number	Product name	Max. system power (W)	Lumen (lm)	Colour temperature (K)	Mått (LxWxH/D, mm)	Colour	IP-class
7020138	HUGIN DT L150 830 HO	70	8190	3000	1481x128x73	White	IP20
7020140	HUGIN DT L150 830 DALI	50	5500	3000	1481x128x73	White	IP20
7020136	HUGIN DT L150 830	50	5500	3000	1481x128x73	White	IP20
7020130	HUGIN DT L120 830	31	3570	3000	1195x128x73	White	IP20
7020137	HUGIN DT L150 840	50	5500	4000	1481x128x73	White	IP20
7020139	HUGIN DT L150 840 HO	70	8190	4000	1481x128x73	White	IP20
7020141	HUGIN DT L150 840 DALI	50	5500	4000	1481x128x73	White	IP20
7020131	HUGIN DT L120 840	31	3570	4000	1195x128x73	White	IP20
7020133	HUGIN DT L120 840 HO	54	6000	4000	1195x128x73	White	IP20
7020135	HUGIN DT L120 840 DALI	31	3570	4000	1195x128x73	White	IP20
7020132	HUGIN DT L120 830 HO	54	6000	3000	1195x128x73	White	IP20
7020134	HUGIN DT L120 830 DALI	31	3570	3000	1195x128x73	White	IP20