



- 5 varieties of optics
- High luminous flux
- For environments with high chemical impact



Beam G2 is an efficient dimmable LED light with high luminous flux. Beam G2 Dali is suitable for environments with high ceilings in, for example, industry, warehouses or supermarkets. Beam G2 Dali Clear is equipped with a clear glass plate that is intended for environments with high chemical impact, such as animal stables. The luminaire is available with 5 variants of optics, which provides an optimal light image for different premises and ceiling heights. As an accessory there are two different reflectors for further opportunity to customize the light. The luminaire has a frame in black lacquered aluminum and can be used in environments with temperatures from -30 - + 50 °C. On request, Beam G2 Dali is available with other wattages. Beam meets the requirements for the D-mark.

Variations

E-number	Product name	Max. system power (W)	Colour temperature (K)	Mått (LxWxD, mm)	Colour	IP-class	Ambient temperature (°C)
7214042	BEAM G2 OPAL DALI	150	4000	-x-x241	Black	IP65	-30 - 50
7214338	BEAM G2 KLAR DALI	150	4000	-x-x241	Black	IP65	-20 - 50
7214039	BEAM G2 50° DALI	150	4000	-x-x241	Black	IP65	-30 - 50
7214040	BEAM G2 90° DALI	150	4000	-x-x241	Black	IP65	-30 - 50
7214041	BEAM G2 120° DALI	150	4000	-x-x241	Black	IP65	-30 - 50