

- Microprismatic diffuser
- Easy to mount
- Available with CRI90



Moln PRO is a thin light panel with a microprismatic diffuser suitable for general lighting in most environments. The light panel has a discreet frame in white lacquered aluminum and is mounted without tools in a suspended ceiling with a visible support profile. Moln PRO can also be suspended at any height with accessories (E7013277) or mounted on the ceiling with accessories (E7013700, E7014513). To change the appearance of the luminaire, the luminaire can be combined with a circular cover plate available as an accessory (E7910385, E7910178). Moln PRO has protection class IP20 above the ceiling and protection class IP44 below the ceiling; when surface mounted in a frame, the entire luminaire is classified as IP20.

The luminaire is available with different light sources; on/off or DALI, with 3000K or 4000K, with CRI80 and CRI90 and in variants with high luminous flux (HO). On/off is supplied with a free-standing, strain-relieved control gear and a 3m cord set with an ungrounded euro plug. DALI is delivered with a freestanding pull-loaded DALI driver and a 3 meter 5-wire cable. For impulse control, all drivers must be of the same make.

On request, Moln PRO is available with different luminous flux, emergency light function or driver with built-in motion sensor.

Variations

| E-number | Product name            | Max. system power (W) | Lumen (lm) | Colour temperature (K) | Beam angle (°) | Mått (LxWxH/D, mm) | Colour |
|----------|-------------------------|-----------------------|------------|------------------------|----------------|--------------------|--------|
| 7014566  | MOLN G2 PRO 830         | 27                    | 3400       | 3000                   | 120            | 595x595x10         | White  |
| 7014567  | MOLN G2 PRO HO 830      | 35                    | 4400       | 3000                   | 120            | 595x595x10         | White  |
| 7014869  | MOLN G2 PRO 840 DALI    | 27                    | 3400       | 4000                   | 120            | 595x595x10         | White  |
| 7014568  | MOLN G2 PRO HO 830 DALI | 35                    | 4400       | 3000                   | 120            | 595x595x10         | White  |
| 7014572  | MOLN G2 PRO 840         | 27                    | 3400       | 4000                   | 120            | 595x595x10         | White  |
| 7014573  | MOLN G2 PRO HO 840      | 35                    | 4400       | 4000                   | 120            | 595x595x10         | White  |
| 7014574  | MOLN G2 PRO HO 840 DALI | 35                    | 4400       | 4000                   | 120            | 595x595x10         | White  |
| 7014867  | MOLN G2 PRO 830 DALI    | 27                    | 3400       | 3000                   | 120            | 595x595x10         | White  |
| 7016439  | MOLN G2 PRO 940         | 35                    | 3500       | 4000                   | 90             | 595x595x10         | White  |
| 7016437  | MOLN G2 PRO 930         | 35                    | 3500       | 3000                   | 90             | 595x595x10         | White  |
| 7016438  | MOLN G2 PRO 930 DALI    | 35                    | 3500       | 3000                   | 90             | 595x595x10         | White  |
| 7016440  | MOLN G2 PRO 940 DALI    | 35                    | 3500       | 4000                   | 90             | 595x595x10         | White  |