



- Impact resistant
- Adjustable power
- True wiring 5G2,5mm²



POP Li66 is an IP66 enclosed luminaire with diffuser and body in impact-resistant polycarbonate (PC), for example for parking garages, workshops or other exposed environments. The luminaire is installed with stainless steel ceiling clips, the accompanying rope bracket or on the wall using a bracket (accessory). Clips between the body and diffuser remain in the body when the diffuser is opened. Overconnection 5G2.5mm² in frame as standard and quick connector between frame and dome/LED makes installation easy.

POP Li66 is available in two different lengths, 1174 and 1454mm, with three different controls, 4000K, with ballast as standard and meets the requirements for D-labeling. On/off has adjustable power and luminous flux in four steps. RS has a built-in motion sensor and adjustable power and luminous flux in four steps. DALI can be connected as DALI or as impulse control (push-dim).

Do you need support?

offert@exaktor.se

0370-69 07 20

exaktor.com/en

Variations

E-number	Product name	Max. system power (W)	Lumen (lm)	Colour temperature (K)	Mått (LxWxH/D, mm)	Colour	IP-class
7217271	POP Li66 L145 840 ÖK Flex	44	4100 – 7200	4000	1454x102x82	Grey	IP66
7217272	POP Li66 L117 840 ÖK RS	33	3000 – 5200	4000	1174x102x82	Grey	IP66
7217273	POP Li66 L145 840 ÖK RS	45	4100 – 7200	4000	1454x102x82	Grey	IP66
7217274	POP Li66 L117 840 ÖK DA	33	2061 – 5200	4000	1174x102x82	Grey	IP66
7217275	POP Li66 L145 840 ÖK DA	0	7000	4000	1454x102x82	Grey	
7217270	POP Li66 L117 840 ÖK Flex	32	3000 – 5200	4000	1174x102x82	Grey	IP66