

- Timeless design
- Steplessly adjustable c-c mounting
- Made in Värnamo, Sweden



TeleLED fits into most environments and has a clean design language with straight lines. The luminaire is painted in structural white with zinc end caps.

Discreet brackets that run in grooves on the sides of the luminaire enable infinitely adjustable c-c throughout the length of the luminaire. As standard, the luminaires are equipped with DALI actuators and can be connected as DALI or as impulse control/Switch DIm. .) TeleLED has a completely luminous surface downwards without dark areas.

TeleLED School is equipped with 3m 5-wire cable. TeleLED Office has an impulse switch that regulates both up and down light simultaneously (DimEasy). 1 short pull turns the luminaire on/off. If you hold the cord down, the luminaire is dimmed. As standard, the luminaire is delivered with a 2.5 m cord holder.

The luminaire is manufactured in Värnamo.

Variations

E-number	Product name	Max. system power (W)	Colour temperature (K)	Mått (LxWxH/D, mm)	Colour	IP-class	Pendant length (mm)
7011567	TeleLED® OFFICE 50W/830 DALI	51	3000	970x103x97	White	IP20	100 – 1400
7011568	TeleLED® SCHOOL 50W/840 DALI	51	4000	970x103x97	White	IP20	100 – 1400
7011569	TeleLED® OFFICE 50W/840 DALI	51	4000	970x103x97	White	IP20	100 – 1400
7011566	TeleLED® SCHOOL 50W/830 DALI	51	3000	970x103x97	White	IP20	100 – 1400